

## HP006 Coupler


Part		Α	н	Maximum
Number	Connection Type	Overall Length	Hex Size	Working Pressure
#	<u>^^^^</u>		$\bigcirc$	
		inch	inch	psi
HP006-0-A9	Type "M" (9/16" - 18 threads)	3.30	1.19	30,000
HP006-0-A12	Type "M" (3/4" - 16 threads)	3.34	1.19	30,000
HP006-0-HM4	1/4" High Pressure Male	3.46	1.19	30,000
HP006-0-HM9	9/16" High Pressure Male	3.70	1.19	30,000
HP006-0-LM6	3/8" Medium Pressure Male	3.54	1.19	20,000
HP006-0-NFB	1/4" NPT Female	3.30	1.19	15,000
HP006-0-NFC	3/8" NPT Female	3.30	1.19	15,000
HP006-0-NMB	1/4" NPT Male	3.40	1.19	15,000
HP006-0-NMC	3/8" NPT Male	3.30	1.19	15,000
HP006-0-NMD	1/2" NPT Male	3.45	1.19	15,000
HP006-0-X13	Low Angle Face Seal (9/16" - 18 threads	3.37	1.19	30,000




HP006-0-HM4




HP006-0-LM6




HP006-0-HM9




HP006-0-A9, HP006-0-A12



HP006-0-X13



HP006-0-NMB, HP006-0-NMC, HP006-0-NMD



HP006-0-NFB, HP006-0-NFC

