



1AYLX – Type “M” female swivel



MATERIAL High strength carbon steel, zinc plated

#	⊙				⌚	A	B	J	↻	
	DN	size	mm	inch					MPa	psi
1AYLX-6-03	5	-03	4.8	3/16	9/16 - 18UNF	66	26	22	180	26,100
1AYLX-6-04	6	-04	6.4	1/4	9/16 - 18UNF	61	29	22	164	23,780
1AYLX-8-05	8	-05	7.9	5/16	3/4 - 16UNF	74	30	27	150	21,750
1AYLX-8-06	10	-06	9.5	3/8	3/4 - 16UNF	70	26	27	140	20,300
1AYLX-11-08	12	-08	12.7	1/2	1 - 12UNF	80	27	32	130	18,850
1AYLX-16-12	20	-12	19.0	3/4	1 5/16-12UNF	82	29	41	100	14,500

1AYLX – Type “M” female swivel



MATERIAL Stainless steel

#	⊙				⌚	A	B	J	↻	
	DN	size	mm	inch					MPa	psi
6AYLX-6-2AC	3	-02	3.2	1/8	9/16 - 18 UNF	64	33	17	220	31,900
1AYLX-6-03C	5	-03	4.8	3/16	9/16 - 18 UNF	67	26	22	180	26,100
1AYLX-8-05C	8	-05	7.9	5/16	3/4 - 16 UNF	70	31	27	150	21,750
1AYLX-8-06C	10	-06	9.5	3/8	3/4 - 16 UNF	70	25	27	140	20,300
1AYLX-11-08C	12	-08	12.7	1/2	1 - 12 UNF	81	27	32	130	18,850
1AYLX-16-12C	20	-12	19.0	3/4	1 5/16-12 UNF	82	29	41	100	14,500
6AYLX-16-16C	25	-16	25.4	1	1 5/16 - 12 UNF	139	52	38	90	13,050